

---

## HGM9320CAN

Item number:	HGM9320CAN
Power supply:	DC8-35V
Product dimension:	237*172*45(mm)
Plane cutout	214*160(mm)
Operation temp	-25 to +70 ?
Weight:	0.85kg
Display	4.3 inches TFT-LCD (480*272)
Operation panel	Silicon Rubber
Language	Chinese & English
Digital Input	8
Relay out put	8
Analogue input	5
AC system	1P2W/2P3W/3P3W/3P4W
Alternator Voltage	(15~360)V(ph-N)
Alternator Frequency	50/60Hz
Monitor Interface	RS485
Programmable Interface	USB/RS485
DC Supply	DC(8?35)V

HGM93XX MPU(CAN) series genset controllers are used for genset automation and monitor control system of single unit to achieve automatic start/stop, data measure, alarm protection and “three remote” (remote control, remote measuring and remote communication). The controller adopts large liquid crystal display (LCD) and selectable Chinese, English or other languages interface with easy and reliable operation.

HGM93XX MPU(CAN) series genset controllers adopt 32 bits micro-processor technology with precision parameters measuring, fixed value adjustment, time setting and threshold adjusting and etc. The majority of parameters can be set using front panel and all the parameters can be set using PC (via USB port) and can be adjusted and monitored with the help of RS485 port. It can be widely used in a number of automatic genset control system with compact structure, simple connections and high reliability.

### Performance and Characteristics

HGM9310 MPU(CAN), used for single automation systems, auto start/stop of the unit are performed with the help of remote signal.

HGM9320 MPU(CAN), has all functions of HGM9310 MPU(CAN) as well as automatic mains failure function (AMF), particularly well suited for single automation systems that include mains and generator.

MORE INFORMATION PLEASE TOWARDS DOWNLOAD THANKS

---

Product link : <https://www.cnfengtop.com/?p=324924>